



# Electric Sump Pump Specification Sheet 1 of 2

Sump Pump	Power rating (kW)	Weight (kg)	Width (mm)	Height (mm)	Solids Passage (mm)	Outlet (inch)
1. Minex	1.6	25	200	616	7.5	2
2. Minette	1.9-2.7	29	240	676	9	3
3. Minor N	4.4	50	286	768	10	4
4. Major N	5.6	50	768	286	10	4
5. Master N	11.7	80	832	346	10	6
6. Matador N	20.0	131	395	954	12	6
7. Minor H	4.4	50	286	768	10	3
8. Major H	5.6	50	768	286	10	3
9. Master H	11.7	80	832	346	10	4
10. Matador H	20.0	131	395	954	12	4
11. Master SH	11.7	98	887	346	10	3



WJ Groundwater operate one of the largest fleets of electrical sump pumps in the Middle East. At the core of WJ fleet are the Grindex drainage sump pumps, a heavy duty pump ideal for construction dewatering. They are robust, power efficient and can be used for pumping dirty water and sewage.

Discharge flows range from 5l/s to 350l/s, and head capacity range from 15m to 100m. Standard (N), high head (H) and super high head (SH) versions are available. The sump pumps connect to a remote starter panel and are powered by generators or 3-phase mains power.

See 'Specification Sheet 2' for high capacity electrical sump pumps. Contact us today for further information.

\*Available for hire with starter panel, discharge hose, power cable, generators, alarms, float-switch, operator and pontoon raft.

